

# Tag Removal Detector



The removal of tags from secured merchandise in the privacy of a fitting room is a major concern for retailers. The Tag Removal Detector is especially designed to detect fitting room fraud while it is happening.

AM technology, installed in the entrance of the store, combined with the RF technology based Tag Removal Detector installed in the fitting rooms and Dual Technology tags, offer a complete store security solution.

The OSTR A D55 Dual Technology tag contains an AM and RF coil and also the shell contains an RF coil. Attached to merchandise, only the AM coil can be detected in the store's entrance, providing anti-shoplifting security. In case the tag and shell are taken apart in the fitting room, the RF coils will be detected by the Tag Removal Detector.

The multicolor LED alarm indicator with integrated buzzer, or alternatively a silent alarm, will notify store personnel when removal of a tag is detected in the fitting room.

The Tag Removal Detector offers remote connectivity, which enables remote service and direct insight in tag removal alarms as well as fitting room usage when the Tag Removal Detector is combined with a movement sensor.

## Unique features

---

Real-time detection of potential fraud in the fitting room

---

Insight in alarms and fitting room usage

---

Remote service enabled

---

Only possible in combination with AM technology in the entrance

---



# Tag Removal Detector

## Features

### Tag Removal Detector

Number of fitting rooms protected by one unit	2
Maximum number of fitting rooms in one store	20
Remote service and management information <sup>1</sup>	●
Selectable notifications for occupied, free and alarm	●
Multicolor alarm lights	●
Buzzer	●
Relay contact for external alarming	●
Input for movement sensor (PIR)	●

## Detection distance <sup>2</sup>

Cross Point OSTRA D55 Dual Technology hard tag (Ø 55 mm)	up to 70 cm
--	-------------

## Specifications

Tag Removal Detector unit dimensions	170 x 113 x 40 mm
Board power	20VDC + synchronization signal
Power over field bus	●
Programmable I/Os / Relays	2 / 2
Weight	250 grams
Alarm Indicator dimensions	50 x 140 x 15 mm

1. In combination with the CrossCONNECT Access Point

2. Tested with Cross Point OSTRA D55 Dual Technology tag. The specified distance is dependent of the size of the antenna loops and the environment.